



Standard Door Sizes

Inside Diameter "A"	Outside Netframe "B"	Throat Opening "C"
1981.2mm [78"]	2032mm [80"]	1362mm [53.63"]
2133.6mm [84"]	2184.4mm [86"]	1467mm [57.75"]
2286mm [90"]	2336.8mm [92"]	1571.6mm [61.88"]
2438.4mm [96"]	2489.2mm [98"]	1676.4mm [66"]
2590.8mm [102"]	2641.6mm [104"]	1782.8mm [70.19"]
2743.2mm [108"]	2794mm [110"]	1887.5mm [74.31"]
2895.6mm [114"]	2946.4mm [116"]	1992.3mm [78.44"]
3048mm [120"]	3098.8mm [122"]	2097.1mm [82.56"]

Options:

- 120V Controls Power Requirements
- Extended Door Heights 2135-3048mm HUC (84-120") (Contact Factory)
- D: 280mm (11") Recessed For Flush Mount BoonAssist
310mm (12.31") Recessed For Under Floor Mount

Installation:

Door Installed Recessed in Floor
 Floor Must Be Dead Level.
 Door Ties to Adjacent Storefront or Curtain-wall System for Lateral Stability.
 Adjacent Construction Not to Bear Down on any Part of Revolving Door.

Vertical Section

