



### Standard Door Sizes

| Inside Diameter "A" | Outside Netframe "B" | Throat Opening "C" |
|---------------------|----------------------|--------------------|
| 1981.2mm [78"]      | 2032mm [80"]         | 1362.2mm [53.63"]  |
| 2133.6mm [84"]      | 2184.4mm [86"]       | 1466.9mm [57.75"]  |
| 2286mm [90"]        | 2336.8mm [92"]       | 1571.8mm [61.88"]  |
| 2438.4mm [96"]      | 2489.2mm [98"]       | 1676.4mm [66"]     |
| 2590.8mm [102"]     | 2641.6mm [104"]      | 1781mm [70.12"]    |
| 2743.2mm [108"]     | 2794mm [110"]        | 1885.7mm [74.24"]  |
| 2895.6mm [114"]     | 2946.4mm [116"]      | 1990.3mm [78.36"]  |
| 3048mm [120"]       | 3098.8mm [122"]      | 2095mm [82.48"]    |

### Options:

- Extended Door Heights 2000 - 3000 mm [84-120"]
- Throat Length 20-36" (Contact Factory)
- Splay Angle 55 degree standard (Contact Factory for 45 degree)
- 1 Piece Ceiling for 2000mm diameter (84")
- 1 Piece Sidewall for 2000 - 3000 mm (84-120") (Contact Factory)
- D - 280 mm (11") recessed for flush mount BoonAssist
- D - 312 mm (12.31") recessed for under floor mount Boon Assist
- Felt Rubber Weather Stripping.

### Installation:

- Door Installed Recessed in Floor
- Floor Must Be Dead Level.
- Door Ties to Adjacent Storefront or Curtain-wall System for Lateral Stability.
- Adjacent Construction Not to Bear Down on any Part of Revolving Door.

