



Standard Size Doors

Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
7'-0"[2130mm]	7'-3"[2210mm]	3'-1 5/8"[955mm]
7'-6"[2285mm]	7'-9"[2360mm]	3'-4 5/8"[1035mm]
8'-0"[2440mm]	8'-3"[2515mm]	3'-7 5/8"[1110mm]
8'-6"[2590mm]	8'-9"[2670mm]	3'-10 5/8"[1185mm]
9'-0"[2745mm]	9'-3"[2820mm]	4'-2 5/8"[1285mm]
9'-6"[2895mm]	9'-9"[2970mm]	4'-5 5/8"[1365mm]
9'-9"[2970mm]	10'-0"[3050mm]	4'-7 1/4"[1415mm]

Options:

- 120V Lights/Controls Power Requirements
- Extended Door Heights (Contact Factory) 7' - 10' HUC (2130-3050mm)
- Extended Canopy Heights (Contact Factory)
- Slidebolt lock
- Medium Style Door Wing
- Herculite Style Door Wing
- Electric Locking with Post Mounted Control
- Horse Hair or Felt Rubber Weather Stripping

Installation:

Door Installs on Finish Floor (No recess, rings, or cutouts required)
 Floor Must Be Dead Level.
 Door Ties to Adjacent Storefront or Curtain-Wall System for Lateral Stability.
 Adjacent Construction Not to Bear Down on any Part of Revolving Door.

