



GENERAL NOTES:

TURNLOCK-200TL = 1 DIRECTION ELECTRICALLY CONTROLLED.
 TURNLOCK-200TL2 = 2 DIRECTIONS ELECTRICALLY CONTROLLED.

MINIMUM PAD SIZE SHOWN. MUST BE LEVEL WITHIN 1/4".

BRACE BARRIER POST AT TOP TO ADJACENT SURFACE.

ALLOW 1" [25.4MM] FOR REMOVAL OF 2PC COVER.

ELECTRICAL NOTES:

POWER SERVICE OPTIONS:

1. 24 VDC
2. 110 VAC SINGLE PHASE
3. 220 VAC SINGLE PHASE 50/60HZ
4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

4 LOCATIONS AVAILABLE FOR CONDUIT ACCESS.

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. BARRIER ASSEMBLY, WELDED - ANODIZED ALUMINUM
2. SHIELD ASSEMBLY, WELDED - ANODIZED ALUMINUM WITH LEXAN PANELS
3. ROTOR ASSEMBLY (6) - ANODIZED ALUMINUM WITH LEXAN ARMS
4. 2 PC CHANNEL COVER - STAINLESS STEEL
5. MECHANISM CHANNEL - POWDERCOATED STEEL
6. BASE PLATE - ANODIZED ALUMINUM
7. BOTTOM BEARING
8. BOTTOM FLANGE
9. ANCHOR BOLTS (18), PROVIDED

POWER AND ACCESS CONTROL CONNECTION (INTERNAL)



