



### Standard Door Sizes

Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
6'-6" [1980MM]	6'-8" [2030MM]	4'-5 1/2" [1360MM]
7'-0" [2135MM]	7'-2" [2185MM]	4'-9 3/4" [1465MM]
7'-6" [2285MM]	7'-8" [2335MM]	5'-2" [1575MM]
8'-0" [2440MM]	8'-2" [2490MM]	5'-6 1/8" [1680MM]
8'-6" [2590MM]	8'-8" [2640MM]	5'-10 3/8" [1790MM]
9'-0" [2745MM]	9'-2" [2795MM]	6'-2 5/8" [1895MM]
9'-6" [2895MM]	9'-8" [2945MM]	6'-6 7/8" [2005MM]
10'-0" [3050MM]	10'-2" [3100MM]	6'-11 1/8" [2110MM]

### Options:

- 110v or 220v mains power
- D: 11" [280mm] recess for flush mount BoonAssist  
12 1/4" [310mm] recessed for under floor mount
- E: Extended door heights 7'-0" to 10'-0" [2135-3050mm]
- BoonAssist cover plate options: square or round stainless steel

### Installation:

- Door installed recessed in floor.
- Power supply from below.
- Door ties to adjacent storefront or curtain-wall system for lateral stability.
- Adjacent construction not to bear down on any part of door.

