



Standard Door Sizes

Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
6'-6" [1980MM]	6'-8" [2060MM]	4'-5 1/2" [1360MM]
7'-0" [2135MM]	7'-2" [2210MM]	4'-9 3/4" [1465MM]
7'-6" [2285MM]	7'-8" [2360MM]	5'-2" [1575MM]
8'-0" [2440MM]	8'-2" [2515MM]	5'-6 1/8" [1680MM]
8'-6" [2590MM]	8'-8" [2670MM]	5'-10 3/8" [1790MM]
9'-0" [2745MM]	9'-2" [2820MM]	6'-2 5/8" [1895MM]
9'-6" [2895MM]	9'-8" [2970MM]	6'-6 7/8" [2005MM]
10'-0" [3050MM]	10'-2" [3124MM]	6'-11 1/8" [2110MM]

Options:

- 110v or 220v mains power requirements
- D: 11" [280mm] recess for flush mount BoonAssist
12 1/4" [310mm] recessed for under floor mount
- E: Extended door heights 7'-0" to 10'-0" [2135-3050mm]
- BoonAssist cover plate options: square or round stainless steel
- Throat length 20-36" (Contact Factory)
- Splay angle 55 degree standard (Contact Factory for 45 Degree)
- 1 piece ceiling for 7' diameter [2135mm]
- 1 piece sidewall for 7'-10' [2135mm - 3050mm] (Contact Factory)
- Felt rubber weather stripping.

Installation:

- Door installed recessed in floor.
- Power supply from below.
- Door ties to adjacent storefront or curtain-wall system for lateral stability.
- Adjacent construction not to bear down on any part of door.