



Standard Size Doors

Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
7'-0" [2135MM]	7'-3" [2210MM]	3'-2 3/4" [985MM]
7'-6" [2285MM]	7'-9" [2360MM]	3'-5 3/4" [1060MM]
8'-0" [2440MM]	8'-3" [2515MM]	3'-8 3/4" [1135MM]
8'-6" [2590MM]	8'-9" [2670MM]	3'-11 3/4" [1215MM]
9'-0" [2745MM]	9'-3" [2820MM]	4'-2 3/4" [1290MM]
9'-6" [2895MM]	9'-9" [2970MM]	4'-5 3/4" [1365MM]
9'-9" [2970MM]	10'-0" [3050MM]	4'-8 3/4" [1440MM]

Options:

- 110V or 220V lights/controls power requirements
- D: extended door heights 7' - 10' [2130-3050mm]
- Extended canopy heights (Contact factory)
- Slidebolt lock
- Medium or herculite style door wing
- Electric Locking with Post Mounted Control
- Horse Hair or Felt Rubber Weather Stripping

Installation:

Door installs on finish floor (No recess, rings, or cutouts required)
 Floor must be dead level.
 Door ties to adjacent storefront or curtain-wall system for lateral stability.
 Adjacent construction not to bear down on any part of revolving door.

