



### Standard Door Sizes

Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
6'-6" [1980MM]	6'-9" [2060MM]	4'-4 5/8" [1335MM]
7'-0" [2135MM]	7'-3" [2210MM]	4'-8 7/8" [1445MM]
7'-6" [2285MM]	7'-9" [2360MM]	5'-1 1/8" [1550MM]
8'-0" [2440MM]	8'-3" [2515MM]	5'-5 3/8" [1660MM]
8'-6" [2590MM]	8'-9" [2670MM]	5'-9 5/8" [1765MM]
9'-0" [2745MM]	9'-3" [2820MM]	6'-1 7/8" [1875MM]
9'-6" [2895MM]	9'-9" [2970MM]	6'-6 1/8" [1985MM]
9'-9" [2970MM]	10'-0" [3050MM]	6'-10 1/4" [2090MM]

### Options:

- 110V or 220V mains power requirements
- Extended canopy heights (Contact factory)
- D: Extended door heights 7' - 10' [2130-3050MM]
- Slidebolt lock
- Medium or herculite style door wing
- Electric locking with post mounted control
- Horse hair or felt rubber weather stripping

### Installation:

Door installs on finish floor (No recess, rings, or cutouts required)  
Floor must be dead level.  
Door ties to adjacent storefront or curtain-wall system for lateral stability.  
Adjacent construction not to bear down on any part of revolving door.

