



Standard Door Sizes

Nominal Diameter	Inside Diameter "A"	Outside Net Frame "B"	Throat Opening "C"
6' 6"	6' 6" [1980MM]	6' 9" [2055MM]	4'-4 5/8" [1335MM]
7' 0"	7' 0" [2135MM]	7' 3" [2210MM]	4'-8 7/8" [1445MM]
7' 6"	7' 6" [2285MM]	7' 9" [2360MM]	5'-1 1/8" [1550MM]
8' 0"	8' 0" [2440MM]	8' 3" [2515MM]	5'-5 3/8" [1660MM]
9' 0"	9' 0" [2745MM]	9' 3" [2820MM]	6'-1 7/8" [1875MM]
10' 0"	9' 9" [2970MM]	10'-0" [3045MM]	6'-8 1/8" [2035MM]

Options:

- Ceiling lights (120 V power from above)
- Extended door heights (Contact factory)
- Extended canopy heights (Contact factory)
- Slidebolt lock
- Medium style door wing
- Electric locking with post mounted control
- One piece sidewall glass

Installation:

Door installs on finish floor (No recess, rings, or cutouts required)
Floor must be dead level.
Door ties to adjacent storefront or curtain-wall system for lateral stability.
Adjacent construction not to bear down on any part of revolving door.

