



GENERAL NOTES:

TURNLOCK-200EL = 1 DIRECTION ELECTRICALLY CONTROLLED.
 TURNLOCK-200EL2 = 2 DIRECTIONS ELECTRICALLY CONTROLLED.

MINIMUM PAD SIZE SHOWN. MUST BE LEVEL WITHIN 1/4".

BRACE BARRIER POST AT TOP TO ADJACENT SURFACE.

ALTERNATE COVERS AVAILABLE.

ELECTRICAL NOTES:

POWER SERVICE OPTIONS:

1. 24 VDC
2. 110 VAC SINGLE PHASE
3. 220 VAC SINGLE PHASE 50/60HZ
4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

4 LOCATIONS AVAILABLE FOR CONDUIT ACCESS.

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. BARRIER ASSEMBLY, WELDED - ANODIZED ALUMINUM
2. SHIELD ASSEMBLY, WELDED - ANODIZED ALUMINUM WITH LEXAN PANELS
3. ROTOR ASSEMBLY (3) - ANODIZED ALUMINUM WITH LEXAN ARMS
4. ROUND CANOPY - STAINLESS STEEL
5. MECHANISM CHANNEL - STAINLESS STEEL
6. BASE PLATE - ANODIZED ALUMINUM
7. BOTTOM BEARING
8. BOTTOM FLANGE
9. ANCHOR BOLTS (9), PROVIDED
10. LOCKING CANOPY ACCESS DOOR (SECURE SIDE)

TURNLOCK-200EL (DIMENSIONS IN INCHES)				
NOMINAL SIZE	A	B	C	D
60	Ø60	60	66	25.41
66	Ø66	66	72	28.38
72	Ø72	72	78	31.38

TURNLOCK-200EL: FULL HEIGHT SECURITY TURNSTILE

Project: CUTSHEET
 Job #: 12/13/2019
 Rev: B
 Rev Date:

Customer:
 Contractor:
 Architect:

By: HM

