

GENERAL NOTES:

- TRILOCK-75:
- MECHANICAL UNIT
 - ONE DIRECTIONS ELECTRICALLY CONTROLLED
 - TWO DIRECTIONS ELECTRICALLY CONTROLLED

OPTIONAL PLATFORM AND RAILING AVAILABLE
 OPTIONAL POWDERCOATING AVAILABLE

ELECTRICAL NOTES:

- POWER SERVICE OPTIONS:
1. 24VDC
 2. 110 VAC SINGLE PHASE
 3. 220 VAC SINGLE PHASE 50/60HZ
 4. 220 VAC DUAL PHASE 50/60HZ

15 MAINS SERVICE REQ'D

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL

CODED NOTES:

1. TOP COVER - STAINLESS STEEL
2. CABINET - STAINLESS STEEL
3. ACCESS DOORS (2) TYP.
4. ARM - STAINLESS STEEL Ø1-1/4" 16GA. (3) TYP
5. COVER LOCK
6. HUB - POWDERCOATED ALUMINUM
7. CONCEALED HINGE

PASSAGE WIDTH & ARM LENGTH		
PASSAGE WIDTH	ARM LENGTH	TRUE ARM LENGTH
18"	17"	15.52
20"	19"	17.52
22"	21"	19.52

*316SS-18" PASSAGE (17" ARM) ONLY

