

GENERAL NOTES:

TRILOCK-75RN

- ONE DIRECTION ELECTRICALLY CONTROLLED
- TWO DIRECTIONS ELECTRICALLY CONTROLLED
- MECHANICAL UNIT

LONGER ARMS AVAILABLE (17" SHOWN).

OPTIONAL PLATFORM AND RAILING AVAILABLE.
OPTIONAL POWDERCOATING AVAILABLE.

ELECTRICAL NOTES:

POWER SERVICE OPTIONS:

1. 24 VDC
2. 110 VAC SINGLE PHASE
3. 220 VAC SINGLE PHASE 50/60HZ
4. 220 VAC DUAL PHASE 50/60HZ

15A MAINS SERVICE REQ'D

AUTHORIZATION, FIRE ALARM REQUIRES DRY CONTACT FROM ACCESS CONTROL.

CODED NOTES:

1. TOP COVER - STAINLESS STEEL
2. CABINET - STAINLESS STEEL
3. ACCESS DOOR - 304 STAINLESS STEEL
4. ARM - STAINLESS STEEL Ø1-1/4" 16GA. (3) TYP.
5. HUB: ANODIZED ALUMINUM
6. REVEAL - 304 STAINLESS STEEL

PASSAGE WIDTH & ARM LENGTH		
PASSAGE WIDTH	ARM LENGTH	TRUE ARM LENGTH
18"	17"	15.76
20"	19"	17.76
22"	21"	19.76

FOOTPRINT SECTION A-A
SCALE 0.09 : 1

